

CITY OF WHITEHALL

RIGHT-OF-WAY, EASEMENT AND/OR
PAVEMENT BREAKING PERMIT

Date: _____

I/We, _____, respectfully request permission to
break the pavement in the right-of-way (R.O.W.), easement, and/or city property at

_____ between _____ and

_____ Streets, for the purpose of:

Sewer Water Gas Telephone Power & Light Other

I/We agree to conform to all rules and regulations set forth in the Ordinance entitled "An Ordinance Governing the Use of Streets, Alleys, and Public Places in the City of Whitehall" as amended.

I/We further agree to pay all costs incidental to the breaking and replacing of said pavement, also to hold the City of Whitehall and its officers and employees harmless from and against any and all claims for damages or other liability that may be brought against it in the completion of this work.

I/we further agree that the placement of the above named utility will be 3 feet or more from any city utility located in that right-of-way.

Contractor hereby agrees to conform to all local ordinances, MDOT, MIOSHA, and OSHA regulations regarding construction standards and safety. Contractor is responsible for calling MISS DIG 3 days prior to beginning work.

Contractor

Granted this _____ day of _____, 20____.

City of Whitehall, Michigan

A copy of the contractor's current insurance must be on file at City Hall prior to issuance of this permit.

WINTER REQUIREMENTS

CONTRACTOR IS RESPONSIBLE FOR THE MAINTENANCE AND REPAIR OF THE STREET CUT UNTIL PROPER AND APPROVED REPAIRS ARE MADE.

CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ROAD SURFACE FOR SAFE TRAFFIC FLOW.

CONTRACTOR MUST FOLLOW REGULATIONS FOR BACKFILLING PER MDOT:

- Proper compaction of below road soils.
- Minimum of 8" gravel, limestone or dolomite.
- Minimum of 3" on secondary streets or 5" on major streets of cold patch.

In the spring, or as soon as possible, hot asphalt repair will be made. Contractor will insure that a proper hot asphalt repair is made to the street. Construction area will be saw cut and cold patch removed for proper road repair.

SUMMER REQUIREMENTS

Contractor will put in 8" gravel, limestone, or dolomite and compact construction area. An overlay of hot asphalt will be made with proper compaction and match to existing street surface. This work will be completed within (10) ten working days of road opening.

Winter work will be hot patched within ten (10) working days of plant opening.

NOTE: City streets will have a 8" gravel, limestone, or dolomite base regardless of existing street construction and a minimum three inch (3") overlay of hot asphalt.